

Keltek Standard Preset Torque Wrench

Model numbers

These are our standard models. All are made to order. We will need your desired torque setting and units.

We also offer metric sizes, and custom tool heads. Please contact us if you don't see what you need.

Preset Torque Wrenches From 3 to 180 inch pounds

Open end tool head

Box end tool head

Hex key tool head

Square drive tool head

Open end tool head from 3 to 180 inch pounds

			Allowable preset torque range (governed by
	Handle	Tool Head	tool head size and
Model	Length	Size	torque handle length
5106	6"	3/16"	3 - 25 in. lbs.
5108	6"	1/4"	3 - 40 in. lbs.
5110	6"	5/16"	3 - 60 in. lbs.
5112	6"	3/8"	3 - 60 in. lbs.
5114	6"	7/16"	3 - 60 in. lbs.
5116	6"	1/2"	3 - 60 in. lbs.
5118	6"	9/16"	3 - 60 in. lbs.
5120	6"	5/8"	3 - 60 in. lbs.
5122	6"	11/16"	3 - 60 in. lbs.
5124	6"	3/4"	3 - 60 in. lbs.
5126	6"	13/16"	3 - 60 in. lbs.
5128	6"	7/8"	3 - 60 in. lbs.
1108	8"	1/4"	20-100 in. lbs.
1110	8"	5/16"	20-100 in. lbs.
1112	8"	3/8"	20-100 in. lbs.
1114	8"	7/16"	20-180 in. lbs.
1116	8"	1/2"	20-180 in. lbs.
1118	8"	9/16"	20-180 in. lbs.
1120	8"	5/8"	20-180 in. lbs.
1122	8"	11/16"	20-180 in. lbs.
1124	8"	3/4"	20-180 in. lbs.
1126	8"	13/16"	20-180 in. lbs.
1128	8"	7/8"	20-180 in. lbs.

Box end tool head from 3 to 180 inch pounds

(default style is 12 pt double offset)

			Allowable preset torque range (governed by
	Handle	Tool Head	tool head size and

Model	Length	Size	torque handle length
5206	6"	3/16"	3 - 25 in. lbs.
5208	6"	1/4"	3 - 40 in. lbs.
5210	6"	5/16"	3 - 60 in. lbs.
5212	6"	3/8"	3 - 60 in. lbs.
5214	6"	7/16"	3 - 60 in. lbs.
5216	6"	1/2"	3 - 60 in. lbs.
5218	6"	9/16"	3 - 60 in. lbs.
5220	6"	5/8"	3 - 60 in. lbs.
5222	6"	11/16"	3 - 60 in. lbs.
5224	6"	3/4"	3 - 60 in. lbs.
5226	6"	13/16"	3 - 60 in. lbs.
5228	6"	7/8"	3 - 60 in. lbs.
1208	8"	1/4"	20-100 in. lbs.
1210	8"	5/16"	20-100 in. lbs.
1212	8"	3/8"	20-100 in. lbs.
1214	8"	7/16"	20-180 in. lbs.
1216	8"	1/2"	20-180 in. lbs.
1218	8"	9/16"	20-180 in. lbs.
1220	8"	5/8"	20-180 in. lbs.
1222	8"	11/16"	20-180 in. lbs.
1224	8"	3/4"	20-180 in. lbs.
1226	8"	13/16"	20-180 in. lbs.
1228	8"	7/8"	20-180 in. lbs.

Hex key tool head from 3 to 180 inch pounds

			Allowable preset torque range (governed by tool head size and torque handle length)
Model	Handle Length	Tool Head Size	
5503	6"	3/32"	3 - 20 in. lbs.
550A	6"	7/64"	3 - 45 in. lbs.
5504	6"	1/8"	3 - 60 in. lbs.
550B	6"	9/64"	3 - 60 in. lbs.
5505	6"	5/32"	3 - 60 in. lbs.
5506	6"	3/16"	3 - 60 in. lbs.
5507	6"	7/32"	3 - 60 in. lbs.
5508	6"	1/4"	3 - 60 in. lbs.
5510	6"	5/16"	3 - 60 in. lbs.
5512	6"	3/8"	3 - 60 in. lbs.
1504	8"	1/8"	20-60 in. lbs.
150B	8"	9/64"	20-80 in. lbs.
1505	8"	5/32"	20-100 in. lbs.
1506	8"	3/16"	20-180 in. lbs.
1507	8"	7/32"	20-180 in. lbs.
1508	8"	1/4"	20-180 in. lbs.
1510	8"	5/16"	20-180 in. lbs.
1512	8"	3/8"	20-180 in. lbs.

Square drive tool head from 3 to 180 inch pounds

			Allowable preset torque range (governed by tool head size and torque handle length)
Model	Handle Length	Tool Head Size	

5308	6"	1/4" Fixed	3 - 60 in. lbs.
5308R	6"	1/4" Ratcheting	3 - 60 in. lbs.
5312	6"	3/8" Fixed	3 - 60 in. lbs.
5312R	6"	3/8" Ratcheting	3 - 60 in. lbs.
5316	6"	1/2" Fixed	3 - 60 in. lbs.
5316R	6"	1/2" Ratcheting	3 - 60 in. lbs.
1308	8"	1/4" Fixed	20-180 in. lbs.
1308R	8"	1/4" Ratcheting	20-180 in. lbs.
1312	8"	3/8" Fixed	20-180 in. lbs.
1312R	8"	3/8" Ratcheting	20-180 in. lbs.
1316	8"	1/2" Fixed	20-180 in. lbs.
1316R	8"	1/2" Ratcheting	20-180 in. lbs.